

RYCO Swivel Joints are ideal for use wherever hose moves, bends or twists. They permit the use of less hose in flexing applications, producing neater space-saving installations and resulting in lower maintenance costs. Compact and lightweight, the RYCO Swivel Joint turns with very low torque under pressure, assuring fluid line flexibility and efficiency of operation.

NOTE: Swivel Joints must not be used as high speed rotary unions, or as load bearing or structural components. They must be connected with a flexible hose on one end. External loads, eg. the weight of the hose and couplings attached to the swivel joint; must be minimised to avoid premature wear and leakage.

Operating Temperature Range: From -40°C to + 100°C (-40°F to + 212°F).

Fluid Compatibility: Mineral / petroleum based hydraulic oils.

SWIVEL JOINT			S37	S36	SEAL KITS SJK
<b>BSP/BSP</b> <b>360° ROTATION</b> <b>10 RPM - NOT CONTINUOUS</b> <b>3000PSI MAX</b>					
<b>THREAD SIZE</b> <b>DASH SIZE</b>		<b>BSPT MALE</b> <b>BSPT MALE</b> <b>90° SWIVEL JOINT</b>	<b>BSPT MALE</b> <b>BSP FEMALE SWIVEL</b> <b>90° SWIVEL JOINTS</b>	<b>REPLACEMENT SEAL KIT</b>	
<b>A</b>	<b>B</b>	<b>DASH SIZE</b>	<b>PART NO</b>	<b>PART NO</b>	
1/2	1/2	-0808	S37-0808	SJK-08	
3/4	3/4	-1212		SJK-12	

SWIVEL JOINT			S131	SEAL KITS RKS
<b>JIC/JIC</b> <b>360° ROTATION</b> <b>20 RPM - NOT CONTINUOUS</b> <b>4000 PSI MAX</b>				
<b>THREAD SIZE</b> <b>DASH SIZE</b>		<b>JIC MALE</b> <b>JIC FEMALE FIXED</b> <b>SWIVEL JOINT</b>	<b>REPLACEMENT SEAL KIT</b>	
<b>A</b>	<b>B</b>	<b>DASH SIZE</b>	<b>PART NO</b>	
1.1/16	1.1/16	-1717	RKS131-1717	
1.5/16	1.5/16	-2121	RKS131-2121	

SWIVEL JOINT			S33	S34	S35	SEAL KITS SJK
<b>JIC/JIC</b> <b>360° ROTATION</b> <b>10 RPM - NOT CONTINUOUS</b> <b>3000 PSI MAX</b>						
<b>THREAD SIZE</b> <b>DASH SIZE</b>		<b>JIC MALE</b> <b>JIC MALE</b> <b>90° SWIVEL JOINT</b>	<b>JIC MALE</b> <b>JIC FEMALE</b> <b>90° SWIVEL JOINT</b>	<b>JIC FEMALE</b> <b>JIC MALE</b> <b>90° SWIVEL JOINT</b>	<b>REPLACEMENT SEAL KIT</b>	
<b>A</b>	<b>B</b>	<b>DASH SIZE</b>	<b>PART NO</b>	<b>PART NO</b>	<b>PART NO</b>	<b>PART NO</b>
7/8	7/8	-1414	S33-1414	S34-1414	S35-1414	SJK-08
1.1/16	1.1/16	-1717	S33-1717	S34-1717	S35-1717	SJK-12